

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	REVISIONS REVISIONS							
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED			
Α		CH'D - 1 BOM INFO PER S.E. CH'D -3 P.F. FROM -43 PER G.E.	5/9/2011	RJC	RW			
В		CH'D TOOL NAME WAS UPPER MODULE LIP SEAL REMOVER IS TOOL, UPPER MODULE LIP SEAL INSTALLER TO MATCH PARTS MANUAL.	11/1/2013	RJC	RW			
1		-1 Ch'd Dim Was 1.62 is 1.59, added b/o info mcmaster-carr #98381a5093 Ch'd Dim Was Ø.187 \pm .563 is limits Ø.1869 to .1874 \pm .56. Ch'd tolerance on non-critical parts.	5/14/2014	DPD	GE			
2	17-0093	UPDATED TO NEW STANDARD. ADDED OEM REF NOTE1 CH'D DIM WAS 2,952 IS 2,95, ADDED MED KNURL NOTE.	4/20/2017	DPD	JAG			





- NOTES: 1. PART OF KIT RBW6305G01531-3G, BOX ONE RBW6305G19631-3G.
- 2. REF. AGUSTA T/N: 3G6305G14031

•	•	•	1		RO	S	2	CE	

TOOL, UPPER MODULE LIP SEAL INSTALLER TITLE

DWG NO. RBW6305G14031-3G


MAT'L	UNLESS OTHERWISE SPECIFIED
IEAT	DIMENSIONS ARE IN INCHES
REAT	.XXX ± .005 FRACTIONS ± 1/8
INISH	.XX ± .01 ANGLES ±.5°
	.X ± .1 SURFACES = 125/
SPEC	1. BREAK ALL SHARP EDGES
DRAWN BY: CLOUGH	.015 x 45° OR .015R

2

2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 UNIT B/O Part # Description Material B/O INFORMATION OR SPECIFICATIONS PG. CHECKED: RJC 04/21/2017 OPPS APPR: AA 05/09/2017 -1 TOP 2 6061 QA APPR: USED ON MODEL JL 05/10/2017 APPROVED: -3 BASE 6061 3 JAG 05/18/2017 AW139 SCALE DATE 1:4 2/4/2011 SHEET 1 OF 3 B/O -5 DOWEL PIN STEEL Ø3/16 X 7/8 (MCMASTER-CARR #98381A509)

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	revisions							
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED			
1		-1 CH'D DIM WAS 1.62 IS 1.59.	5/14/2014	DPD	GE			
2	17-0093	-1 CH'D DIM WAS 2,952 IS 2,95. ADDED MED KNURL NOTE.	4/20/2017	DPD	JAG			



TITLE TOOL, UPPER MODULE LIP SEAL INSTALLER DWG NO. REV RBW6305G14031-3G-1 MAT'L 6061 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

.XXX ± .005 FRACTIONS ± 1/8

.XX + .01 ANGLES ±.5°


.X ± .1 SURFACES = 125/ TREAT
FINISH CLEAR ANODIZE SPEC MIL-A-8625F, TYPE II, CLASS I 1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DRAWN BY: CLOUGH CHECKED: RJC 04/21/2017 OPPS APPR: AA 05/09/2017 QA APPR: USED ON MODEL JL 05/10/2017 APPROVED: JAG 05/18/2017 AW139 SCALE DATE 1:3 2/4/2011 SHEET 2 OF 3


(1-

TOP

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

		REVISIONS			
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
Α		CH'D -3 P.F. FROM -43 PER G.E.	5/6/2011	RJC	RW
1		-3 CH'D DIM WAS Ø.187 $$.563 IS LIMITS Ø.1869 TO .1874 $$.56.	5/14/2014	DPD	GE







TOOL, UPPER MODULE
LIP SEAL INSTALLER

RBW6305G14031-3G-3

MAT'L 6061 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

.XXX ± .005 FRACTIONS ± 1/8

.XX ± .01 ANGLES ± .5°

.X ± .1 SURFACES = 125/ HEAT TREAT FINISH CLEAR ANODIZE QA APPR: USED ON MODEL JL 05/10/2017 APPROVED: JAG 05/18/2017 AW139 SCALE DATE 1:4 2/4/2011 SHEET 3 OF 3

(-3)

BASE